


Raychem QTVR

SELF-REGULATING HEATING CABLE

HEATING CABLE CONSTRUCTION



1.4 mm² nickel plated copper conductors (10 and 15QTVR2-CT)
 2.3 mm² nickel plated copper conductors (20QTVR2-CT)

Electrical heat-tracing for process temperature maintenance applications up to 110°C which are not subject to steam cleaning.

The QTVR family of self-regulating, parallel circuit heating cables is used for process temperature maintenance of pipes and vessels.

It can also be used for frost protection of large pipes and for applications requiring medium temperature exposure capability.




APPLICATION

Area classification	Hazardous, Zone 1, Zone 2 (Gas), Zone 21, Zone 22 (Dust) Ordinary
Traced surface type	Carbon steel Stainless steel Painted or unpainted metal
Chemical resistance	Organics and corrosives For aggressive organics and corrosives consult your local Pentair representative

SUPPLY VOLTAGE

	230 Vac (Contact your local Pentair representative for data on other voltages)
--	--

APPROVALS

	<p>The QTVR heating cables are approved for use in hazardous areas by PTB and Baseefa Ltd. PTB 09 ATEX 1116 X & Baseefa06ATEX0185X  II 2G Ex e II T4 &  II 2D Ex tD A21 IP66 T130°C IECEX PTB 09.0057X & IECEX BAS 06.0045X Ex e II T4 & Ex tD A21 IP66 T130°C</p> <p>The QTVR heating cables are approved by DNV for use on ships and mobile offshore units. DNV Certificate No. E-11564</p> <p> (Russia, Kazakhstan, Belarus) For other countries contact your local Pentair representative.</p>
--	---


SPECIFICATIONS

Maximum maintain or continuous exposure temperature (power on/off)	110°C
Maximum intermittent exposure temperature (power on/off)	110°C
Temperature classification	T4
Minimum installation temperature	-60°C
Minimum bend radius	at 20°C: 13 mm at -60°C: 35 mm

THERMAL OUTPUT RATING

Nominal power output at 230 Vac on insulated steel pipes

- A 20QTVR2-CT**
B 15QTVR2-CT
C 10QTVR2-CT



	10QTVR2-CT	15QTVR2-CT	20QTVR2-CT
Nominal power output (W/m at 10°C)	38	51	64

PRODUCT DIMENSIONS (NOMINAL) AND WEIGHT

	10QTVR2-CT	15QTVR2-CT	20QTVR2-CT
Thickness (mm)	4.5	4.5	5.1
Width (mm)	11.8	11.8	14.0
Weight (g/m)	126	126	180

MAXIMUM CIRCUIT LENGTH BASED ON TYPE 'C' CIRCUIT BREAKERS ACCORDING TO EN 60898

Electrical protection sizing	Start-up temperature	Maximum heating cable length per circuit (m)		
		10QTVR2-CT	15QTVR2-CT	20QTVR2-CT
16 A	-20°C	65	63	47
	+10°C	80	63	47
25 A	-20°C	95	75	60
	+10°C	115	95	75
32 A	-20°C	115	100	75
	+10°C	115	100	95
40 A	-20°C	115	100	95
	+10°C	115	100	115

The above numbers are for circuit length estimation only. For more detailed information please use the Pentair TraceCalc software or contact your local Pentair representative.

Pentair requires the use of a 30 mA residual current device to provide maximum safety and protection from fire.

Where design results in higher leakage current, the preferred trip level for adjustable devices is 30 mA above any inherent capacitive leakage characteristic of the heater as specified by the trace heater supplier or alternatively, the next common available trip level for non adjustable devices, with a maximum of 300 mA. All safety aspects need to be proven.

ORDERING DETAILS

Part description	10QTVR2-CT	15QTVR2-CT	20QTVR2-CT
Part No.	391991-000	040615-000	988967-000

COMPONENTS

Pentair offers a full range of components for power connections, splices and end seals.

These components must be used to ensure proper functioning of the product and compliance with electrical requirements.