

Experience the freedom: One ventilator, one circuit, multiple sites of care

LTV[®] 1200 Series ventilator (*patients 5 kg to adult*)



The ventilation tools you need throughout the continuum of care for patients 5 kg and above

At a fraction of the size of comparably equipped systems, the LTV 1200 Series ventilator provides the ventilation tools you need, where you need them: critical care, emergency departments and emergency preparedness, patient transport and long-term care.

A wide range of ventilation therapies for patients

The LTV ventilator offers both invasive and noninvasive modes of ventilation in Pressure Control, Pressure Support, Volume Control and Spontaneous Breath Types. Studies show the use of noninvasive ventilation, when clinically appropriate, reduces incidents of ventilator-associated pneumonia (VAP), improves weaning success and reduces total days of ventilation.

Patient presets for quick initiation of ventilation


Choose Infant, Pediatric or Adult to quickly configure initial ventilation before optimizing settings for each patient's needs. This feature is proven to be simple and effective for emergency set-up.

Unique Spontaneous Breathing Trial (SBT)

The SBT feature enhances the clinician's effectiveness during weaning with the potential to save time and money in the process. The SBT works using Rapid Shallow Breathing Index (RSBI) criteria to assess a patient's ability to be weaned. In addition, clinicians can optimize trial settings to each individual patient, ensuring the most favorable levels of support throughout the weaning process. The SBT feature allows the patient to synchronize their breathing pattern with Pressure Support and/or continuous positive airway pressure (CPAP) with variable rise time, flow termination and time termination.

Oxygen (O₂) resource management tool

The O₂ Conserve feature reduces O₂ consumption when the time and place of care require it. This feature extends the sometimes scarce resource of O₂ during transport or emergencies and may be turned off when O₂ resources are again in full supply.



Enhanced monitoring capabilities

Upgrade the system with the LTM Graphics Monitor, and the LTV 1200 Series ventilator provides clinicians with even more comprehensive monitoring of critical patient-ventilator interaction. The graphics monitoring package displays real-time pressure, flow and volume curves with adjustable cursors for accurate breath data measurement. The LTM monitor also displays flow/volume loops and volume/pressure loops to enhance patient assessment. Patient data can be trended for up to 24 hours for clinical evaluation.

Customizable system configurations

The LTV 1200 Series ventilator system can be custom configured with a wide range of accessories to meet the needs of the most demanding care environments.

Accessories	Part number
LTM Graphics Monitor package	17650-001
Floor stand	10611
Short crossbar	11451
Long crossbar	11452
Circuit support arm	11501
Humidifier pole	11453
Utility basket	11450
SprintPack Lithium-Ion Power System	19222-001
SprintPack bracket	19096-001
SprintPack transport pack	19102-001

Specifications

Physical specifications with boots (approx.)	
Weight	14.5 lb (6.5 kg)
Height	3.25" (8.4 cm)
Width	10.5" (27 cm)
Depth	13.5" (38 cm)
Variable alarms	
Apnea interval	10–60 sec
High pressure limit	5–100 cmH ₂ O
Low peak pressure	Off, 1–60 cmH ₂ O
Low minute volume	Off, 0.1–99 L
High PEEP	Off, 3–20 cmH ₂ O above set PEEP
Low PEEP	Off, -3– -20 cmH ₂ O below set PEEP
High rate	Off, 5–80 BPM
Alarm volume	60–85 dBA

Controls	
Power	On/Standby
Ventilation modes	Control, Assist/Control, SIMV/CPAP and NPPV
Breath types	VC, PC, PS and Spontaneous
Breath rate	0–80 BPM
Tidal volume	50–2,000 mL
Inspiratory time	0.3–9.9 sec
PC/PS/Spont. flow	160 LPM
Pressure control	1–99 cmH ₂ O
Pressure support	1–60 cmH ₂ O
Sensitivity	Off, 1–9 LPM
O ₂ %	21–100%
O ₂ flush	1–3 min
Low pressure O ₂	On/Off
PEEP/CPAP	0–20 cmH ₂ O
Insp/Exp hold	6 sec max
Manual breath	1x current settings
Control lock	Easy or hard unlock options

Monitors and indicators	
Peak inspiratory pressure	0–120 cmH ₂ O
Mean airway pressure	0–99 cmH ₂ O
PEEP	0–99 cmH ₂ O
Breath rate	0–250 BPM
Airway pressure display	-10–108 cmH ₂ O
Exhaled tidal volume	0–4,000 mL
Exhaled minute volume	0–99.9 L
I:E ratio	99:1–1:99
Calculated peak flow	10–100 LPM
AutoPEEP	0–100 cmH ₂ O
Static compliance	1–99 mL/cmH ₂ O
Patient effort	Green LED

Fixed alarms	
Disconnect/Sense	
External power low and lost	
High and low O ₂ inlet pressure	
Internal battery low and empty	
Ventilator inoperative	

Extended features	
SBT	
Ventilator presets (<i>Infant, Pediatric and Adult</i>)	
Variable rise time	
Variable flow termination	
Variable time termination	
Pressure control flow termination	
Leak compensation	
O ₂ conserve	
O ₂ cylinder duration calculation	
O ₂ flush	
Apnea interval	
Pneumatic specifications	
High pressure O ₂ source	40–80 PSIG (2.8–5.5 bar)
Low pressure O ₂ source	< 80 LPM, < 10 PSIG
Power indicators	
External power	Green and amber LEDs
Battery charge status	Green, amber and red LEDs
Battery level	Green, amber and red LEDs
Power specifications	
Ventilator input 11–15 VDC	
AC adapter input 100–250 VAC	
50–60 Hz	
Environmental specifications	
Operating temperature	5–40 °C (40–104 °F)
Storage temperature	-20–60 °C (-4–140 °F)
Operating humidity	15–95% relative
Storage humidity	10–95% relative
Shock compliance	MIL-STD-810F
Vibration compliance	MIL-STD-810F
Standards and regulatory compliance	
RTCA/DO-160F	
ANSI/UL STD 60601-1	
IEC 60601-2-12	
cETLus	
CAN/CSA C22.2 STD NO. 601.1	

For more information, contact Customer Service for the United States at **800.754.1914** and **+1 763.398.8300** internationally.

LTV 1200 product specifications are subject to change. Consult your sales representative or CareFusion if you have any questions regarding updates to the product specifications.



 **CAUTION:** U.S. Federal Law restricts this device to sale by or on the order of a physician.

CareFusion
22745 Savi Ranch Parkway
Yorba Linda, CA 92887

800.231.2466 toll-free
714.283.2228 tel
714.283.8493 fax

carefusion.com

